



Specifications Philips LED Downlight LuxSpace Mini
DN560B VLC-E 9W 1350lm 80D - 830 Warm White |
164mm - Aluminium Reflector - Dali Dimmable

[View Product](#)

General Information

| | |
|--------------------------|----------------------------------|
| SKU | 238706 |
| EAN | 8718699970529 |
| Brand | Philips |
| Manufacturer Name | DN560B LED12S/830 PSD-VLC-E C WH |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 70000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Wattage | 9 |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable |
| Colour Code | 830 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Driver Included | Yes |
| Beam Angle (degree) | 80 |

| | |
|--------------------------|--------------------------|
| Luminous Flux (Lumen) | 1350 |
| Luminous Efficacy (lm/W) | 146 |
| Power factor | >0.90 |
| Installation Depth (mm) | 86 |
| Unified Glare Rating | < 22 - for general areas |
| Optical Cover | PC (Polycarbonate) |
| Finish of Reflector | PC (Polycarbonate) |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|-------------------|
| EOC8 | 97052900 |
| Mounting Method | Recessed |
| Cut out (mm) | 150 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature | +10 to +25 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Series | DN560B |

Dimensions

Height (mm)

Why Any-lamp?

74

Diameter (mm)

164



Order from the **largest lighting specialist** in Europe



Customised quotation

Sensor Information



Up to **7 years warranty**



Easy return process

Type of sensor

No Sensor