



Specifications Philips LED Panel
FlexBlend SP342P 42,5W 4500lm - 940
Cool White | 150x20cm - UGR <19 -
Dali Dimmable - Best Colour
Rendering

[View Product](#)

General Information

| | |
|--------------------------|------------------------------------|
| SKU | 238839 |
| EAN | 8719514103733 |
| Brand | Philips |
| Manufacturer Name | SP342P 45S/940 PSD MLO SMT L150 WH |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 50000 |
| Series | SP342P |

Technical Information

| | |
|-----------------------------|--------------------|
| Technology | LED Integrated |
| Replaces (Watt) | 2x58 |
| Wattage | 42.5 |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable with Dali |
| Colour Code | 940 Cool White |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra) | 90-99 |
| Colour of Light | White |
| Light colour options | Single Color |
| Luminous Flux (Lumen) | 4500 |

| | |
|--------------------------|-------------------|
| Luminous Efficacy (lm/W) | 106 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Fixture Connection | Terminal, 5-pole |
| Driver Included | Yes |
| Power factor | >0.90 |
| Product Type Category | LED Panel |

Fixture Information

| | |
|-----------------------|--------------------------------|
| EOC8 | 10373300 |
| Mounting Method | Suspended |
| Unified Glare Rating | < 19 - for offices and schools |
| Optical Cover | PC (Polycarbonate) |
| Operating Temperature | -10 to +40 |
| Emergency Lighting | No Emergency Unit |
| Colour of the Fixture | White |
| Housing | Steel |
| Colour of material | White |

Dimensions

| | |
|----------------|----------|
| LED panel size | 150x20cm |
| Length (mm) | 1470 |
| Width (mm) | 200 |
| Height (mm) | 73 |

Why Any-lamp?



Order from the **largest lighting specialist** in Europe



Customised quotation

Sensor Information



Up to **7 years warranty**



Easy return process

| | |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|